



TECHNICAL DATA

FLOW RATE	MAX. 1,750 GPM (397 m ³ /hr)
SCREEN SIZE	____ MICRON
SCREEN AREA	7.0 SQ. FEET
WORKING TEMPERATURE	MAX. 200 °F
WORKING PRESSURE	MAX. 150 PSI
EMPTY WEIGHT	~585 LBS.
FULL WEIGHT	~1,110 LBS.

NOZZLE	CONNECTION	TYPE	SIZE	RATING	TOLERANCES (UNLESS OTHERWISE SPECIFIED)		 2672 S. LA CIENEGA BLVD. LOS ANGELES, CA 90034 MAIN: (310) 839-2828 FAX: (310) 839-6878
A1	SERVICE PORT	FLANGED	3.5" ASA	CL. #150 F.F. w/ Blind	FRAC. ±1/16	ANGLE ±1°	
A2	PRESSURE RELEASE	THREADED	1" NPT(2)		.X ±.1		
K1	HIGH PRESSURE CONN.	THREADED	1/4" NPT(2)	CLASS #150 F.F.S.O.	.XX ±.05		
K2	LOW PRESSURE CONN.	THREADED	1/4" NPT(2)	CLASS #150 F.F.S.O.	.XXX ±.010	DRAWN BY: S. PERKINSON	
K3	HYDRAULIC CONN.	THREADED	1/4" NPT(2)			DATE: 07/06/11	TITLE: ABW10-P FILTER, CUT DRAWING
N1	INLET	FLANGED	10" ASA			SCALE: 1:14	
N2	OUTLET	FLANGED	10" ASA			SHEET: 1 OF 1	ABW-10P-CUT-01
N3	FLUSH OUTLET	THREADED	2" NPT				REV N/A