




REVISIONS				
REV.	ZONE	DESCRIPTION	DATE	INITIAL

SERVICE AREA
48.5" x 12.75"

TECHNICAL DATA

FLOW RATE	MAX. 800 GPM (182 m ³ /hr)
SCREEN SIZE	___ MICRON
SCREEN AREA	8.0 SQ. FEET
WORKING TEMPERATURE	MAX. 200 °F
WORKING PRESSURE	MAX. 150 PSI
EMPTY WEIGHT	~335 LBS.
FULL WEIGHT	~635 LBS.

NOZZLE	CONNECTION	TYPE	SIZE	RATING	TOLERANCES (UNLESS OTHERWISE SPECIFIED)		 Automatic Filters Inc. 2672 S. LA CIENEGA BLVD. LOS ANGELES, CA 90034 MAIN: (310) 839-2828 FAX: (310) 839-6878	
A1	SERVICE PORT	FLANGED	3.5" ASA	CL. #150 F.F. w/ Blind	FRAC. ±1/16	ANGLE ±1°		
A2	PRESSURE RELEASE	THREADED	1" NPT(2)		.X ±.1			
K1	HIGH PRESSURE CONN.	THREADED	1/4" NPT(2)	CLASS #150 F.F.S.O. CLASS #150 F.F.S.O.	.XX ±.05			
K2	LOW PRESSURE CONN.	THREADED	1/4" NPT(2)		.XXX ±.010			
K3	HYDRAULIC CONN.	THREADED	1/4" NPT(2)					
N1	INLET	FLANGED	6" ASA		MATERIAL: SST		TITLE:	
N2	OUTLET	FLANGED	6" ASA		DRAWN BY: S. PERKINSON		ABW6-XLP FILTER, CUT DRAWING	
N3	FLUSH OUTLET	THREADED	2" NPT		DATE: 06/28/11	DRAWING NUMBER	REV	
					SCALE: 1:14	SHEET: 1 OF 1	ABW-6XLP-CUT-01	N/A