



REVISIONS				
REV.	ZONE	DESCRIPTION	DATE	INITIAL

**TECHNICAL DATA**

FLOW RATE	MAX. 1,500 GPM (341 m <sup>3</sup> /hr)
SCREEN SIZE	___ MICRON
SCREEN AREA	7.0 SQ. FEET
MAXIMUM TEMPERATURE	MAX. 200 °F
MAXIMUM PRESSURE	MAX. 150 PSI
EMPTY WEIGHT	~250 LBS.
FULL WEIGHT	~650 LBS.

**SIDE VIEW**

NOZZLE	CONNECTION	TYPE	SIZE	RATING	TOLERANCES (UNLESS OTHERWISE SPECIFIED)	 2672 S. LA CIENEGA BLVD. LOS ANGELES, CA 90034 MAIN: (310) 839-2828 FAX: (310) 839-6878	
K1	HIGH PRESSURE CONN.	THREADED	1/4" NPT(2)				FRAC. ±1/16      ANGLE ±1° .X ±.1 .XX ±.05 .XXX ±.010
K2	LOW PRESSURE CONN.	THREADED	1/4" NPT			<b>TITLE:</b> MTF8-S FILTER, CUT DRAWING	
K3	HYDRAULIC CONN.	THREADED	1/4" NPT				
N1	INLET	FLANGED	8" ASA	CLASS #150 F.F.S.O.	<b>MATERIAL:</b> SST	<b>DRAWING NUMBER</b> MTF-8S-CUT-01	
N2	OUTLET	FLANGED	8" ASA	CLASS #150 F.F.S.O.	<b>DRAWN BY:</b> S. PERKINSON		
N3	FLUSH OUTLET	THREADED	2" NPT		<b>DATE:</b> 11/14/11	<b>REV</b>	
					<b>SCALE:</b> 1:13	<b>SHEET:</b> 1 OF 1	N/A