



REVISIONS				
ZONE	REV	DESCRIPTION	DATE	APPROVED

TECHNICAL DATA

Flow Rate	Max. 1750 GPM
Screen Size	___ Micron
Screen Area	7.0 Sq.Ft.
Working Temp.	200 deg. F
Working Pressure	150 PSI
Empty Weight	500 lbs.
Full Weight	___ lbs.

NOZZLE	CONNECTION	TYPE OF CONNECTION	SIZE	RATING
A1	Service Port	Flanged	3.5" ASA	150 lbs. F.F. w/ Blind
A2	Pressure Release	Threaded	1" NPT(2)	
K1	Hi. Press. Conn.	Threaded	1/4" NPT(2)	
K2	Low Press. Conn.	Threaded	1/4" NPT(2)	
K3	Hydraulic Conn.	Threaded	1/4" NPT(2)	
N1	Inlet	Flanged	8" ASA	150 lbs. F.F.
N2	Outlet	Flanged	8" ASA	150 lbs. F.F.
N3	Flushoutlet	Threaded	2" NPT	

<small>UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES DECIMALS ANGULAR .XX + .05 ± 0.5 DEG. .XXX + .01</small>		AUTOMATIC FILTERS, INC. 2672 S. LA CIENEGA BLVD. LOS ANGELES, CA 90034 (310) 839-2828 FAX (310) 839-6878		
		TITLE <h2 style="text-align: center;">ABW8-SP Filter</h2>		
DRAWN Daniel Stenberg	DATE 6-20-05	SIZE A	DWG NO. ABW8-SP	REV 0
CHECKED		scale 1:14		SHEET OF
DESIGN				