



TECHNICAL DATA

Flow Rate	Max.10,000 GPM
Screen Size	___ Micron
Screen Area	22.0 sq.ft.
Working Temp.	200 deg. F
Working Pressure	150 PSI
Empty Weight	2500 lbs.
Full Weight	---- lbs.

NOZZLE	CONNECTION	TYPE OF CONNECTION	SIZE	RATING
A1	Service Port	Flanged	4" ASA	150 lbs. F.F. w/Blind
A2	Service Port	Flanged	4" ASA(2)	150 lbs. F.F. w/Blind
K1	Hi. Press. Conn.	Threaded	1/4" NPT (2)	
K2	Low Press. Conn.	Threaded	1/4" NPT (2)	
K3	Flushoutlet Conn.	Threaded	1/4" NPT(2)	
N1	Inlet	Flanged	24" ASA	150 lbs. F.F.
N2	Outlet	Flanged	24" ASA	150 lbs. F.F.
N3	Flushoutlet	Threaded	2" NPT	

<small>UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES</small> <small>DECIMALS      ANGULAR</small> <small>.XX ± .05      ± 05 DEG</small> <small>.XXX ± .01</small>		<b>AUTOMATIC FILTERS, INC.</b> 2672 S. LA CIENEGA BLVD. LOS ANGELES, CA 90034 (310) 839-2828 FAX (310) 839-6878		
		TITLE <h2 style="text-align: center;">HDL 24-SP</h2>		
DRAWN Daniel Stenberg	DATE 3-26-06	SIZE A	DWG NO. HDL24-SP-2	REV 0
CHECKED	DESIGN	NOT TO SCALE		SHEET OF