



REVISIONS				
REV.	ZONE	DESCRIPTION	DATE	INITIAL

FRONT VIEW

SIDE VIEW

BACK VIEW

TECHNICAL DATA

FLOW RATE	MAX. 300 GPM (68 m ³ /hr)
SCREEN SIZE	___ MICRON
SCREEN AREA	2.0 SQ. FEET
WORKING TEMPERATURE	MAX. 200 °F
WORKING PRESSURE	MAX. 150 PSI
EMPTY WEIGHT	~100 LBS.
FULL WEIGHT	~150 LBS.

NOZZLE	CONNECTION	TYPE	SIZE	RATING
A1	SERVICE PORT	FLANGED	12.75"	
K1	HIGH PRESSURE CONN.	THREADED	1/4" NPT(2)	
K2	LOW PRESSURE CONN.	THREADED	1/4" NPT(2)	
N1	INLET	FLANGED	3" ASA	CLASS #150 F.F.S.O.
N2	OUTLET	FLANGED	3" ASA	CLASS #150 F.F.S.O.
N3	FLUSH OUTLET	THREADED	2" NPT	

TOLERANCES (UNLESS OTHERWISE SPECIFIED)

FRAC. ±1/16	ANGLE ±1°
.X ±.1	
.XX ±.05	
.XXX ±.010	
MATERIAL: SST	
DRAWN BY: S. PERKINSON	
DATE: 10/12/11	
SCALE: 1:8	SHEET: 1 OF 1

TEKLEEN
Automatic Filters Inc.
2672 S. LA CIENEGA BLVD.
LOS ANGELES, CA 90034
MAIN: (310) 839-2828
FAX: (310) 839-6878

TITLE: CSF3 FILTER, CUT DRAWING

DRAWING NUMBER	REV
CSF-3-CUT-01	N/A