



REVISIONS				
REV.	ZONE	DESCRIPTION	DATE	INITIAL

**TECHNICAL DATA**

FLOW RATE	MAX. 1,500 GPM (341 m <sup>3</sup> /hr)
SCREEN SIZE	___ MICRON
SCREEN AREA	7.0 SQ. FEET
MAXIMUM TEMPERATURE	MAX. 200 °F
MAXIMUM PRESSURE	MAX. 150 PSI
EMPTY WEIGHT	~250 LBS.
FULL WEIGHT	~650 LBS.

NOZZLE	CONNECTION	TYPE	SIZE	RATING
K1	HIGH PRESSURE CONN.	THREADED	1/4" NPT(2)	CLASS #150 F.F.S.O.
K2	LOW PRESSURE CONN.	THREADED	1/4" NPT	
K3	HYDRAULIC CONN.	THREADED	1/4" NPT	CLASS #150 F.F.S.O.
N1	INLET	FLANGED	6" ASA	
N2	OUTLET	FLANGED	6" ASA	
N3	FLUSH OUTLET	THREADED	2" NPT	

**TOLERANCES (UNLESS OTHERWISE SPECIFIED)**

FRAC. ±1/16	ANGLE ±1°
.X ±.1	
.XX ±.05	
.XXX ±.010	

**TEKLEEN**  
Automatic Filters Inc.  
2672 S. LA CIENEGA BLVD.  
LOS ANGELES, CA 90034  
MAIN: (310) 839-2828  
FAX: (310) 839-6878

<b>MATERIAL:</b> SST
<b>DRAWN BY:</b> S. PERKINSON
<b>DATE:</b> 11/11/11
<b>SCALE:</b> 1:13

<b>TITLE:</b> MTF6-S FILTER, CUT DRAWING	
<b>DRAWING NUMBER</b>	<b>REV</b>
MTF-6S-CUT-01	N/A